## Product data sheet Characteristics

# 9001KP38LGG31 PILOT LIGHT 120V 30MM TYPE K +OPTIONS

Product availability: Stock - Normally stocked in distribution facility



Price\*: 153.00 USD



#### Main

Range of product	Harmony 9001K	
Product or component type	Pilot light	
Device short name	9001K	

#### Complementary

Main		
Range of product	Harmony 9001K	
Product or component type	Pilot light	
Device short name	9001K	
Complementary		
Bezel material	Chromium plated metal	
Mounting diameter	1.18 in (30 mm)	
Shape of signaling unit head	Round	
Lens type	Fresnel plastic	
Cap/Operator or lens colour	Green	
Light source	Green LED	
Bulb base	BA 9s	
Light block supply	Direct 120 V AC/DC	
Connections - terminals	Screw clamp terminals, 1 x 0.222 x 1.5 mm² IEC 60947-1	
Tightening torque	7.08 lbf.in (0.8 N.m) IEC 60947-1	
Shape of screw head	Cross slotted	
Operating position	Any position	
[Ui] rated insulation voltage	250 V 2)IEC 60947-1	
[Uimp] rated impulse withstand voltage	2.5 kV IEC 60947-1	
Short-circuit protection	10 A cartridge fuse IEC 60947-5-1	
[Ith] conventional free air thermal current	10 A	
CAD overall width	2.13 in (54 mm)	
CAD overall height	2.76 in (70 mm)	
CAD overall depth	1.65 in (42 mm)	
Net Weight	0.30 lb(US) (0.134 kg)	

<sup>\*</sup> Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

#### Environment

Standards	EN/IEC 60947-5-1
Standards	CSA C22.2 No 14
	UL 508
	EN/IEC 60947-5-4
	JIS C 852
	EN/IEC 60947-1
	JIS C8201-5-1
	JIS C8201-1
Product certifications	UL 508
	NEMA
Protective treatment	TC
Ambient air temperature for storage	-40158 °F (-4070 °C)
Ambient air temperature for operation	-13158 °F (-2570 °C)
Vibration resistance	7 gn 2500 Hz)IEC 60068-2-6
Shock resistance	50 gn IEC 60068-2-27
Overvoltage category	Class II IEC 61140
IP degree of protection	IP66 IEC 60529
NEMA degree of protection	NEMA 1
	NEMA 12
	NEMA 13
	NEMA 2
	NEMA 3
	NEMA 3R
	NEMA 4
	NEMA 6

#### Ordering and shipping details

Cracing and ompping act	ano
Category	21426 - 9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	03389110917505
Nbr. of units in pkg.	1
Package weight(Lbs)	4.80 oz (136.078 g)
Returnability	Yes
Country of origin	MX

## Packing Units

•		
Unit Type of Package 1	PCE	
Package 1 Height	2.20 in (5.588 cm)	
Package 1 width	3.60 in (9.144 cm)	
Package 1 Length	1.80 in (4.572 cm)	

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty 18 months