



SPECIFICATIONS:	
UL STYLE:	CMX / AWM 2463
CABLE JACKET MATERIAL:	TPE- Teal
CABLE DIAMETER:	0.26" [6.6mm]
COND. JACKET MATERIAL:	High density polyethylene
INS. COND. DIAMETER:	.048" [1.2mm] nom.
COND. STRANDING:	24AWG - 7/32 Stranded tinned copper
PAIRING:	Grn x Grn/Wht , Org x Wht/Org
SHIELDS:	Tinned Copper Braid (75% Coverage) & foil polyester (100% Coverage)
WEIGHT:	Nom: 34#/Mft
RoHS?:	Yes
ELECTRICAL REQUIREMENTS:	
CAT 5e	
MECHANICAL REQUIREMENTS:	
EXTRUSION STYLE:	PRESSURE EXTRUSION
TEMPERATURE:	-40°C - +80°C
FLEX LIFE:	1MM cycles @ 10x cable OD
	10MM cycles @ 20x cable OD

PAIR EQUIVALENCE:

- 1 WHITE/ORANGE ORANGE
- 2 WHITE/GREEN GREEN

TABLE A	
P/N	LENGTH
60CWS01-0250	250' [76m]
60CWS01-0500	500' [152m]
60CWS01-1000	1000' [305m]

Cable supplied on a single spool.
1 break allowed for lengths of 1000' or more with no piece being shorter than 250'

UNLESS OTHERWISE SPECIFIED:	DRAWN BY	JJH
DIMENSIONS ARE IN INCHES AND [MM]	DRAWN DATE	05/03/2018
	CHECKED BY	ADM
	CHECK DATE	05/03/2018
MATERIAL	COMMENTS:	
FINISH		
DO NOT SCALE DRAWING		

MENCOM CORPORATION		
TITLE: 2 PR 24AWG TEAL CAT5E CBL w/SHLD		
SIZE B	DWG. NO. 60CSW01-ZZ	REV A
SCALE: 3:1	WEIGHT:	SHEET 1 OF 1

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF MENCOM CORPORATION. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF MENCOM CORPORATION IS PROHIBITED.