
## Vacuum generator VN-07-M-T2-PI2-VI2-RI2 Part number: 526111

**FESTO** 





## **Data sheet**

| Feature                                       | Value                                         |
|-----------------------------------------------|-----------------------------------------------|
| Nominal width of Laval nozzle                 | 0.7 mm                                        |
| Width dimension                               | 10 mm                                         |
| Type code                                     | VN                                            |
| Mounting position                             | Any                                           |
| Ejector characteristics                       | High vacuum<br>Inline                         |
| Design                                        | T-shape                                       |
| Symbol                                        | 00991491                                      |
| Operating pressure for max. suction rate      | 7 bar                                         |
| Operating pressure                            | 1 bar 8 bar                                   |
| Operating pressure for max. vacuum            | 5.8 bar                                       |
| Max. vacuum                                   | 86 %                                          |
| Nominal operating pressure                    | 6 bar                                         |
| Max. suction rate with respect to atmosphere  | 13.5 l/min                                    |
| Air supply time at nominal operating pressure | 2.1 s                                         |
| Operating medium                              | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Information on operating and pilot media      | Operation with oil lubrication not possible   |
| Corrosion resistance class (CRC)              | 2 - Moderate corrosion stress                 |
| Temperature of medium                         | 0 °C 60 °C                                    |
| Ambient temperature                           | 0 °C 60 °C                                    |
| Max. tightening torque                        | 0.5 Nm                                        |
| Product weight                                | 13 g                                          |
| Type of mounting                              | With through-hole<br>With accessories         |
| Pneumatic connection 1                        | M5                                            |
| Pneumatic connection 3                        | M5                                            |
| Vacuum connection                             | M5                                            |
| Material of connecting thread                 | Wrought aluminum alloy, anodized              |
| Note on materials                             | Free of copper and PTFE<br>RoHS-compliant     |
| Seals material                                | NBR                                           |
| Female nozzle material                        | POM                                           |
| Housing material                              | POM-reinforced                                |
| Material of jet nozzle                        | Wrought aluminum alloy                        |