
Vacuum suction cup ESS-150-SN Part number: 189326





Data sheet

| Feature | Value |
|---|--|
| Min. workpiece radius | 480 mm |
| Nominal width | 10 mm |
| Suction cup diameter | 150 mm |
| Suction cup volume | 173.826 cm ³ |
| Type code | ESS |
| Connection position | Тор |
| Mounting position | Any |
| Symbol | 00991485 |
| Classification of suction cup holder | Size 6 |
| Suction cup shape | Round, flat |
| Operating pressure | 0 bar 0.95 bar |
| Nominal operating pressure | -0.7 bar |
| Operating medium | Atmospheric air based on ISO 8573-1:2010 [7:-:-] |
| Corrosion resistance class (CRC) | 1 - Low corrosion stress |
| For use in the food industry | See supplementary material information |
| Ambient temperature | -10 °C 70 °C |
| Holding force at nominal operating pressure | 900 N |
| Lateral force at nominal operating pressure | 675 N |
| Product weight | 719 g |
| Type of mounting | Via vacuum connection |
| Vacuum connection | M20x2 |
| Color | Black |
| Shore hardness | 50 +/- 5 |
| Material of screwed trunnion | NBR Steel, nickel-plated Steel, galvanized and chrome-plated |
| Note on materials | Free of copper and PTFE RoHS-compliant |
| Suction cup material | NBR |

FESTO