
## Vacuum suction cup ESS-15-SS Part number: 189291







## **Data sheet**

| Feature                                     | Value   |
|---|---|
| Min. workpiece radius                       | 35 mm   |
| Nominal width                               | 2 mm  |
| Suction cup diameter                        | 15 mm   |
| Suction cup volume                          | 0.208 cm <sup>3</sup>   |
| Type code                                   | ESS   |
| Connection position                         | Тор   |
| Mounting position                           | Any   |
| Symbol                                      | 00991485  |
| Classification of suction cup holder        | Size 3  |
| Suction cup shape                           | Round, flat   |
| Operating pressure                          | 0 bar 0.95 bar  |
| Nominal operating pressure                  | -0.7 bar  |
| Operating medium                            | Atmospheric air based on ISO 8573-1:2010 [7:-:-]                                    |
| Corrosion resistance class (CRC)            | 1 - Low corrosion stress  |
| For use in the food industry                | See supplementary material information  |
| Ambient temperature                         | -30 °C 180 °C   |
| Holding force at nominal operating pressure | 8.5 N   |
| Lateral force at nominal operating pressure | 6.5 N   |
| Product weight                              | 1.9 g   |
| Type of mounting                            | Via vacuum connection   |
| Vacuum connection                           | M4  |
| Color                                       | Transparent   |
| Shore hardness                              | 50 +/- 5  |
| Material of screwed trunnion                | Brass, nickel-plated  |
| Note on materials                           | Free of copper and PTFE Contains paint-wetting impairment substances RoHS-compliant |
| Suction cup material                        | VMQ (silicone)  |