


Filter regulator MS6N-LFR-1/2-D6-ERM-AS

Part number: 531294

FESTO



Data sheet

| Feature | Value |
|----------------------------------|--|
| Size | 6 |
| For use in the food industry | See supplementary material information |
| Type code | MS6N-LFR |
| Series | MS |
| Actuator lock | Rotary knob with detent can be closed with accessories |
| Mounting position | Vertical +/- 5° |
| Grade of filtration | 40 µm |
| Condensate drain | Manually rotating |
| Design | Filter regulator with pressure gauge |
| Max. condensate volume | 38 ml |
| Controller function | Outlet pressure constant With secondary exhausting |
| Bowl guard | Plastic bowl guard |
| Symbol | 00991589 |
| Pressure gauge | with pressure gauge |
| Operating pressure | 0.8 bar ... 20 bar |
| Pressure regulation range | 0.3 bar ... 7 bar |
| Max. pressure hysteresis | 0.25 bar |
| Standard nominal flow rate | 6200 l/min |
| Operating medium | Compressed air as per ISO 8573-1:2010 [-:4:-] Inert gas |
| Corrosion resistance class (CRC) | 2 - Moderate corrosion stress |
| Storage temperature | -10 °C ... 60 °C |
| Air quality class at the output | Compressed air as per ISO 8573-1:2010 [7:4:4] |
| Temperature of medium | -10 °C ... 60 °C |
| Ambient temperature | -10 °C ... 60 °C |
| Product weight | 875 g |
| Type of mounting | Optionally: Front panel mounting Line installation With accessories |
| Pneumatic connection 1 | 1/2 NPT |
| Pneumatic connection 2 | 1/2 NPT |
| Note on materials | RoHS-compliant |
| Material of operator panel | PA POM |

| Feature | Value |
|--------------------------------|-------------------|
| Seals material | NBR |
| Compressed air filter material | PE |
| Housing material | Die-cast aluminum |
| Diaphragm material | NBR |
| Material of bowl | PC |
| Separating disc material | POM |