


Ball valve

VZBE-1-T-63-F-3L-F05-V15V15

Part number: 4834292

FESTO



Data sheet

| Feature | Value |
|---|--|
| Type code | VZBE |
| Seat seal material | PTFE |
| Design | 3-way ball valve Drilled L hole |
| Actuation type | Mechanical |
| Sealing principle | Soft |
| Mounting position | Any |
| Type of mounting | Line installation |
| Fitting connection | 1 NPT |
| Switching position indication | Slot direction = flow direction |
| Flange hole pattern | F05 |
| Inside diameter | 20 mm |
| Nominal width DN | 25 |
| Valve function | 3/2 |
| Flow direction | Reversible |
| Nominal pressure of fitting PN | 63 |
| Breakaway torque at differential pressure, nominal pressure, fitting PN | 25.2 Nm |
| Based on norm | ASME B1.20.1 ISO 5211 |
| Symbol | 00991888 |
| Medium | Vapor Compressed air as per ISO 8573-1:2010 [-:--] Inert gas Water Neutral liquids |
| Temperature of medium | -20 °C ... 200 °C |
| Flow rate Kv type L | 4.1 m ³ /h |
| Note on materials | Contains paint-wetting impairment substances RoHS-compliant |
| Housing material | Cast stainless steel |
| Material number of housing | 1.4408 |

| Feature | Value |
|-------------------------------------|--|
| Seals material | PTFE |
| Ball material | Cast stainless steel |
| Material number for ball | 1.4408 |
| Shaft material | High-alloy stainless steel |
| Material number for shaft | 1.4401 |
| Product weight | 1618 g |
| Certification | CRN |
| Corrosion resistance class (CRC) | 4 - Particularly high corrosion stress |
| Explosion prevention and protection | Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX) |