



# Connecting cable NEBM-H7G2-E-2.5-Q14N-LE2

Part number: 5219205

FESTO



## Data sheet

Feature	Value
Type code	NEBM
Nominal conductor cross section	AWG20
Cable designation	Without label holder
Electrical connection 1, function	Field device end
Electrical connection 1, design	Rectangular
Electrical connection 1, connection type	Socket
Electrical connection 1, cable outlet	Straight
Electrical connection 1, connection technology	Connection diagram H7, coded for motor brake
Electrical connection 1, number of pins/wires	2
Electrical connection 1, occupied pins/wires	2
Electrical connection for input 1, connection pattern	00995791
Electrical connection 2, function	Control side
Electrical connection 2, connection type	Cable
Electrical connection 2, connection technology	Open end
Electrical connection 2, number of pins/wires	2
Electrical connection 2, occupied pins/wires	2
DC operating voltage range	0 V ... 30 V
Operating voltage range AC	0 V ... 30 V
Current rating at 40°C	5 A
Surge resistance	2 kV
Cable length	2.5 m
Cable characteristic	Suitable for energy chains
Connector cable test conditions	Test conditions on request
Bending radius, fixed cable installation	≥27 mm
Bending radius, flexible cable installation	≥55 mm
Cable diameter	5.1 mm
Cable design	2 x 0.51 mm <sup>2</sup>
Nominal conductor cross section	0.51 mm <sup>2</sup>
Wire ends	Cable end sleeve
Degree of protection	IP20
Note on degree of protection	In mounted state
Ambient temperature	-40 °C ... 80 °C
Ambient temperature with flexible cable installation	-10 °C ... 80 °C
CE marking (see declaration of conformity)	As per EU RoHS directive
Note on materials	Contains paint-wetting impairment substances RoHS-compliant

<b>Feature</b>	<b>Value</b>
Contamination level	3
Corrosion resistance class (CRC)	0 - No corrosion stress
Material of cable sheath	PVC
Color cable sheath	Black
Housing material	PA
Housing colour	White
Insulating sheath material	PVC