

# Electrical subbase VAVE-K1-7-5YL1-LR

Part number: 8115100

FESTO



## Data sheet

Feature	Value
Contamination level	2
Insulating sheath material	PVC
Permissible voltage fluctuations	+/- 10 %
Size	7
Bending radius, flexible cable installation	≥16.5 mm
Bending radius, fixed cable installation	≥11 mm
Overvoltage category	II
Type code	VAVE
Mounting position	Any
Cable characteristic	Basic
Reverse polarity protection	for operating voltage
Additional functions	Holding current reduction
Signal status display	LED
DC operating voltage range	12 V ... 26 V
Nominal operating voltage DC	24 V
CE marking (see declaration of conformity)	As per EU EMC directive
Corrosion resistance class (CRC)	0 - No corrosion stress
Storage temperature	-20 °C ... 70 °C
Degree of protection	IP40
Ambient temperature	0 °C ... 50 °C
Certification	RCM compliance mark
Product weight	3.3 g
Electrical connection	2-pin Twin wire Open end
Cable design	2 x 0.08 mm <sup>2</sup>
Cable diameter	1.1 mm
Cable length	0.5 m
Protective earth connection	Not available
Type of mounting	Push-on Engaging
Housing colour	Black
Note on materials	RoHS-compliant
Housing material	PA-reinforced PC