

# Servo motor EMMS-AS-140-LK-HS-RS

Part number: 560903

FESTO



## Data sheet

Feature	Value
Number of pole pairs	6
Type code	EMMS-AS
Rotor position sensor	Absolute encoder, single-turn
Rotor position sensor interface	EnDat® 22
Rotor position sensor measuring principle	Inductive
Temperature monitoring	PTC resistor
Max. rotational speed	2460 1/min
Nominal rotary speed	2000 1/min
Insulation protection class	F
Motor constants	2.72 Nm/A
Motor nominal power	4420 W
DC nominal voltage	565 V
Motor nominal current	7.8 A
Rotor position sensor resolution	18 bit
Phase-phase winding resistance	1.41 Ohm
Winding inductance phase-phase	13.44 mH
Type of winding switch	Star inside
Peak current	20 A
Voltage constant, phase-to-phase	162.39 mVmin
Rating class according to EN 60034-1	S1
CE marking (see declaration of conformity)	As per EU EMC directive As per EU low voltage directive
Corrosion resistance class (CRC)	2 - Moderate corrosion stress
Storage temperature	-20 °C ... 60 °C
Relative air humidity	0 - 90 %
Degree of protection	IP54
Ambient temperature	-10 °C ... 40 °C
Certification	RCM compliance mark c UL us - Recognized (OL)
Total output inertia moment	19.027 kgcm <sup>2</sup>
Nominal torque	20.05 Nm
Peak torque	48.8 Nm
Stall torque	25.48 Nm
Permissible axial shaft load	200 N
Permissible radial shaft load	1060 N
MTTF, subcomponent	76 years, rotor position sensor

<b>Feature</b>	<b>Value</b>
MTTFd, subcomponent	152 years, rotor position sensor
Product weight	16200 g
Electrical connection technology	Plug
Note on materials	RoHS-compliant
Conforms to standard	IEC 60034
Featherkey shaft design	DIN 6885 A 8 x 7 x 40