


Angle seat valve VZXA-B-TS7-2 1/2"-M2-V14T-5.6-M-90-26-V4

FESTO

Part number: 8060554



Data sheet

Feature	Value
Type code	VZXA
Certificate issuing authority	CRNOC20829.5C German Technical Control Board (TÜV) 968/V 1039.00/18
Safety integrity level (SIL)	SIL 2
PFH	1.36E-7
PFD	5.95E-4
Certification	CRN
Operating pressure	0.5 MPa ... 0.7 MPa
Medium pressure	0 MPa ... 0.56 MPa
Operating pressure	72.5 psi ... 101.5 psi
Use in exterior area	wettergeschützte Einsatzorte Klasse C1 in Anlehnung an IEC 60654-1
Design	Poppet valve with diaphragm actuator
Actuation type	Pneumatic
Mounting position	Any
Type of mounting	Line installation
Cable connection	Threaded sleeve 2 1/2 as per ANSI/ASME B 1.20.1
Valve function	2/2
Flow direction	Non-reversible
Medium pressure	0 bar ... 5.6 bar
Reset method	Mechanical spring
Type of control	Externally controlled
Pneumatic connection	Internal thread G1/8
Operating pressure	5 bar ... 7 bar
Symbol	00995582
Medium	Vapor Hydraulic fluid based on mineral oil Inert gas Mineral oil Water Filtered compressed air, 200 µm filter mesh Neutral liquids
Flow direction	Under valve seat, for gaseous and liquid media
Control of the medium	On/off mode
Operating medium	Compressed air as per ISO 8573-1:2010 [7:4:4]
Max. viscosity	600 mm ² /s

Feature	Value
Temperature of medium	-10 °C ... 180 °C
Ambient temperature	0 °C ... 60 °C
Flow rate Kv	77.9 m³/h
Note on materials	Contains paint-wetting impairment substances RoHS-compliant
Valve housing material	Cast stainless steel
Material number, fitting housing	ASTM A351-CF3M
Seals material	NBR
Spindle seal material	PTFE
Seat seal material	PTFE
Product weight	10700 g
CE marking (see declaration of conformity)	as per EU machinery directive
Actuator size	90 mm
Stroke	26 mm
Control function	Closed by spring force, NC
Position sensing	With mechanical indicator
Drive housing material	Cast stainless steel
Material number, drive housing	1.4408
Explosion prevention and protection	Zone 1 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 22 (ATEX)
Storage temperature	-10 °C ... 60 °C
Degree of protection	IP65 IP67
Piston rod material	High-alloy stainless steel
Cover material	Cast stainless steel